

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1.-2. (Canceled)

3. (Previously Presented) Method in accordance with claim 11, wherein the air jet is directed into the cabin from a ceiling area.

4. (Canceled)

5. (Previously Presented) Method in accordance with claim 11, wherein, as the temperature of the air jet rises, its impulse is increased.

6.-7. (Canceled)

8. (Previously Presented) Device in accordance with claim 22, wherein the temperature sensor includes a shape memory alloy.

9. (Previously Presented) Device in accordance with claim 22, wherein the temperature sensor has a bi-metallic element.

10. (Previously Presented) Device in accordance with claim 22, further comprising
a second temperature sensor adapted to measure the temperature of the air jet at a
location spaced away from the guide pipe.

11. (Currently Amended) Method for air-conditioning an aircraft cabin, comprising:
directing at least one air jet into the aircraft cabin with a guide pipe;
measuring the temperature of the air jet with a temperature sensor having a temperature-
dependent form;
altering an angle of the air jet with respect to a vertical direction via rotation of a rotation
device according to a change of form of the temperature sensor, wherein the angle of the air jet
with respect to the vertical direction is ~~continuously~~ steplessly variable within a range of 10° to
90° based on the change of form of the temperature sensor such that, as the temperature of the air
jet rises, the angle of the air jet is made smaller; and
altering an impulse of the air jet according to the change of form of the temperature
sensor by changing a cross-section of an outlet in communication with the guide pipe.

12.-21. (Canceled)

22. (Currently Amended) Device for air-conditioning an aircraft cabin comprising:

a rotation device;

a guide pipe adapted to direct at least one air jet into the aircraft cabin; and

a temperature sensor having a temperature-dependent form, the temperature sensor

operating to:

measure the temperature of the at least one air jet,

actuate rotation of the rotation device to alter an angle of the air jet with respect to

a vertical direction, wherein the angle of the air jet is ~~continuously~~ steplessly variable

within a range of 10° to 90° based on the change of form of the temperature sensor, such

that, as the temperature of the air jet rises, the angle is made smaller, and

alter an impulse of the air jet according to the change of form of the temperature

sensor by actuating a change in the cross-section of an outlet in communication with the guide pipe.